

KATANA

TradeGrade Incorporated

Quality Tires for Trucks

Katana Tradegrade Incorporated now offers quality tires for Elf, Forward, 10-Wheeler, and Trailer Trucks.

300

(8.25R20-16PR)

- Ideal for Elf and Forward Trucks
- Resistant to Cuts and Stone Retention
- Wide tread for longer lifespan and uniform tread wear
- Excellent Stability and Traction when Driving

SIZE	P.R.	LI & SS	Diameter	Section Width	Std. Rim	Tread Depth	Load Capacity	Inflation Pressure
			(mm)	(mm)		(mm)	(kg)	(kPa)
6.50R16LT	12	110/105 L	749	182	5.50F	10.0	1060/925	670
7.00R16LT	14	118/114 L	775	202	5.50F	13.0	1320/1180	770
7.50R16LT	16	124/120 L	801	220	6.00G	12.5	1600/1400	870
8.25R16LT	16	128/124 M	851	233	6.50H	12.5	1800/1600	770
8.25R20	16	139/137 L	963	233	6.50	14.5	2430/2300	930
9.00R20	16	144/142 L	1018	260	7.00	15.5	2800/2650	900
10.00R20	18	149/146 L	1049	278	7.50	16.5	3250/3000	930
11.00R20	18	152/149 L	1083	290	8.00	17.0	3550/3250	930
12.00R20	18	154/151 L	1119	312	8.50	17.5	3750/3450	830
12.00R24	20	160/157 K	1210	310	8.50	14.5	4500/4125	900
11R22.5	16	146/143 M	1049	275	8.25	15.5	3000/2725	830
12R22.5	18	152/149 M	1082	298	9.00	17.0	3550/3250	930
13R22.5	18	154/151 L	1124	300	9.75	17.5	3750/3450	830
315/80R22.5	20	157/154 M	1072	310	9.00	17.0	4125/3750	900



366

(11R22.5-16PR)

- Ideal 10 - wheeler and trailer trucks
- Has enhanced pattern to resist trapping of stones
- Has an exceptional tire life span
- Designed for city and highway driving

SIZE	P.R.	LI & SS	Diameter	Section Width	Std. Rim	Tread Depth	Load Capacity	Inflation Pressure
			(mm)	(mm)		(mm)	(kg)	(kPa)
8R22.5	14	130/128 M	936	210	6.00	13.5	1900/1800	830
9R22.5	16	139/137 M	971	232	6.75	14.5	2430/2300	930
10R22.5	16	144/142 M	1015	252	7.50	15.5	2800/2650	900
11R22.5	16	146/143 M	1051	268	8.25	16.5	3000/2725	830
11R24.5	16	149/146 M	1103	275	8.25	16.5	3250/3000	830
12R22.5	18	152/149 M	1081	298	9.00	15.0	3550/3250	930
13R22.5	18	154/151 L	1122	300	9.75	16.5	3750/3450	830
205/75R17.5	14	124/122 M	749	212	6.00	12.5	1600/1500	760
215/75R17.5	14	126/124 M	761	222	6.00	12.5	1700/1600	700
	16	128/126 M	761	222	6.00	12.5	2180/2060	860
225/75R17.5	16	129/127 M	776	222	6.75	12.5	1850/1750	830
235/75R17.5	16	132/130 M	792	242	6.75	13.0	2000/1900	775
	18	143/141 J	792	242	6.75	13.0	2725/2575	875
245/70R17.5	16	136/134 M	781	249	7.50	12.5	2240/2120	850
	18	143/141 J	781	249	7.50	12.5	2725/2575	900
225/70R19.5	14	128/126 M	804	225	6.75	13.0	1800/1700	760
245/70R19.5	16	136/134 M	769	249	7.50	12.5	2240/2120	830
	18	143/141 J	769	249	7.50	12.5	2725/2575	875
265/70R19.5	16	140/138 M	866	259	7.50	14.0	2500/2360	830
	18	143/141 J	866	259	7.50	14.0	2725/2575	850
285/70R19.5	16	146/144 M	888	287	8.25	14.0	3000/2800	900
	18	150/148 J	888	287	8.25	14.0	3350/3150	900
255/70R22.5	14	138/134 M	926	245	7.50	13.0	2360/2120	760
	16	140/137 M	926	245	7.50	13.0	2500/2300	830
275/70R22.5	18	148/145 M	956	278	8.25	16.5	3150/3900	900
295/80R22.5	18	154/151 M	1038	298	9.00	16.5	3750/3450	900
315/70R22.5	18	156/150 L	1011	311	9.00	15.5	3750/3350	900
315/80R22.5	20	157/154 M	1071	314	9.00	16.5	4125/3750	900
7.50R16	16	124/120 L	801	218	6.00G	12.5	1600/1400	870
9.5R17.5	18	143/141 J	840	234	6.75	14	2725/2575	875
275/70R22.5	18	148/145 M	956	278	8.25	16.5	3150/2900	900

